



3G-6200n

150Mbps Wireless 3G Broadband Router with Print Server



Shares 3G/3.5G or xDSL Internet connection or Printer

The 3G-6200n is a multi-function wireless broadband router. When connecting either a 3G or 3.5G USB modem card* to 3G-6200n, all network (wired / wireless) users can share 3G/3.5G Internet connection. The 3G-6200n can support 3G/3.5G speeds up to 7.2Mbps and comes with a built-in Ethernet WAN port for Cable modem or xDSL modem. When connected to a xDSL/Cable broadband, 3G-6200n will enable the xDSL/Cable broadband connection automatically when 3G/3.5G Internet connection is not available. 3G-6200n USB port can also function as a print server. When you connect with a USB printer, the device can be a print server allowing user to share printer through the network.

Extensive Internet Connection Sharing

With the built in NAT (Network Address Translation) function, the Edimax 3G-6200n allows up to 253 wired or wireless clients to simultaneously share an Internet connection.

High Performance Hardware Design and Impressive Data Transmission Rate via IEEE802.11n

Edimax 3G-6200n is a high speed solution that complies with wireless IEEE 802.11b/g, and is compatible with IEEE 802.11n standard. When fine-tuned to operate using the wireless 802.11n technology, 3G-6200n wireless data transmission rate can reach up to 150Mbps – a coverage 3 times better than a standard 802.11g/b router. This router is a high performance Internet sharing router with 3G function, which enables multiple users to download files at same time.

Easy setup with EZMax Multi-language wizard

A unique multi-language setup wizard is included in the installation CD. You can setup the router to the Internet within minutes by following the simple animated steps.

Hardware WPS (Wi-Fi Protected Setup) and Wireless on/off Button

The WPS button lets you activate the wireless protection. One-Click WPS button helps you setup a secure wireless network in a snap. 3G-6200n features a control button on its back panel to enable the easy switching on and off of the Wi-Fi wireless connection. When you want to use only wired connection, you can simply pause the Wi-Fi option by pressing the button without making any extra setting.

* Please check the 3G/3.5G USB modem card compatible list.



This equipment is intended to be used in all Europe and EFTA countries. Hantek Edimax Technology declares that this product is in conformity with the European R&TTE Directive (1999/5/EC). A declaration of conformity is available on www.edimax.com

FEATURES AND TECHNICAL SPECIFICATIONS

HARDWARE INTERFACE	MANAGEMENT	FREQUENCY & ANTENNA
<ul style="list-style-type: none"> One WAN + Four LAN 10/100Mbps UTP Ports One USB 2.0 for 3G/3.5G USB Modem or Printer One High Gain 3dBi Detachable Antenna LED Indicators: Power, WLAN, WAN, 3G, and Link/Activity WPS/Reset button Switch for wireless on/off 	<ul style="list-style-type: none"> Supports Remote Management System Status and Security Log (Web Interface) Firmware Upgradeable 14 languages User Interface 	<ul style="list-style-type: none"> 2.400 ~ 2.4835 GHz 3dBi
WAN	INSTALLATION	MEMORY
<ul style="list-style-type: none"> Supports 3G/3.5G (UMTS/HSDPA/CDMA) Supports cable/xDSL modem Ethernet WAN protocol: PPPoE/Static IP/PPTP/Dynamic IP/L2TP/Telstra Big Pond 	<ul style="list-style-type: none"> 16-language EZMax Setup Wizard to setup Internet connection, SSID, wireless security and firmware upgrade 	<ul style="list-style-type: none"> 4 MB NOR Flash 32 MB SDRAM
SECURITY	Output POWER & RECEIVE SENSITIVITY	HUMIDITY & TEMPERATURE
<ul style="list-style-type: none"> NAT/NAPT IP Sharing 64/128-bit WEP Encryption and WPA-PSK, WPA2-PSK security DHCP Server/Client MAC/IP Filter and URL Blocking SPI Anti-Dos Firewall 	<ul style="list-style-type: none"> 11n: 16±1dBm 11g: 16±1dBm 11b: 18±1dBm 11n (40MHz): -68dBm, 11n (20MHz): -71dBm, 11g: -74dBm, 11b: -87dBm 	<ul style="list-style-type: none"> 10-90% (Non-condensing) 0°C ~45°C
FUNCTIONS	DIMENSIONS & POWER ADAPTER	CERTIFICATIONS
<ul style="list-style-type: none"> Supports Print Server Port Triggering for Special Applications DDNS (DynDNS, TZO), WMM and QoS Virtual Server and DMZ Static Routing and UPnP VPN Pass Through (IPSec/PPTP) Schedule Control 	<ul style="list-style-type: none"> 179 (W) x 133 (D) x 25 (H) mm DC 12V, 1A 	<ul style="list-style-type: none"> CE, FCC, WiFi

NETWORK SETUP DIAGRAM AND RELATED PRODUCTS

An example of how the 3G-6200n can be setup:

- Connect the 3G/3.5G USB modem card to 3G-6200n router USB port **
- Connect a computer to the LAN port and setup the Internet connection by running the multi-language setup wizard.
- Share the Internet connection by connecting wired or wireless computers.

** You can connect 3G-6200n router WAN port to your Ethernet (RJ45) cable/xDSL modem as a backup.

