



# 150Mbps N Wireless ADSL2+ Modem Router



WBR-6601

H/W Version: 1

## Save space, modem and wireless router in one device

WBR-6601 N Wireless Modem Router integrates an ADSL2+ modem and wireless broadband router in one device, allowing you to easily share your high speed ADSL2+ Internet connection over your wired or wireless local network. Easily connect your PCs or network devices in the home or office.

## N 11n wireless technology = 6x the speed

Using LevelOne "N technology", users enjoy 6 times the speed, and wider coverage of 11g wireless technology. And with a maximum theoretical throughput of 150Mbps the LevelOne WBR-6601 is

an ideal solution for all wireless networking: internet surfing, streaming video and music, sharing files, surveillance and more.

## Secure and protected

Do you worry about the security of your network? With LevelOne's WBR-6601 things have never been easier. It has advanced Firewall and Filtering functions to prevent any unwanted access from the Web.

## Easy Setup

With the quick and easy setup wizard means you'll have your Internet and computers up and running with a few simple clicks.



1. LED Indicators
2. WAN Interface
3. LAN Interface
4. Reset Button
5. Power Jack

## Key Features

- 4-Port switch with 10/100Mbps auto-negotiation and MDI/MDI-X supported
- Conforms to IEEE 802.11b/g standards, and compliant to 802.11n specification
- Allows LAN users to access Internet through Network Address Translation (NAT, IP sharing) simultaneously
- Integrated with bridge/router functionality
- Integrated with Firewall functionality
- Web management for easy configuration and status monitoring
- WEP, WPA/WPA2 ,802.1x supported
- Support Wi-Fi Protected Setup (WPS) technology

## Works Well With



**WUA-0614**  
150Mbps N Wireless USB Adapter



**GNS-2000**  
2-Bay Gigabit Network Storage

## Technical Specification

### LAN/WAN Specification

#### Support Standard

IEEE802.3, IEEE 802.3u 10/100Base-TX, IEEE802.3ab, Auto Negotiation, Auto MDIX

#### Interface

- Connector: RJ45 for LAN, RJ-11 for WAN
- Number of Port: 1 WAN + 4 LAN
- 100BASE-TX/10BASE-T Auto
- Standard: Full Duplex/Half Duplex Auto
- MDI/MDI-X Change: Auto MDI/MDI-X

#### Recommended Cable

- 100BASE-TX: Category 5 or more
- 10BASE-T: Category 3x or more

### Wireless LAN Specification

#### Support Standard

IEEE 802.11b; IEEE 802.11g; IEEE 802.11n

#### Wi-Fi Compliant

WPA/WPA2 Personal

#### Wireless Frequency:

2.400 ~ 2.4835GHz

#### Transmit Output Power

802.11b: 17~18 dBm (Average)

802.11g: 14dBm (Average)

802.11n:

HT40 mode:14Bm (Average)

HT20 mode:14dBm(Average)

#### Transfer Rate

- IEEE802.11b:11M/5.5M/2M/1M

- IEEE802.11g:54M/48M/36M/24M/18M/12M/11M/9M/6M

- IEEE802.11n:802.11n 40MHz mode: 135/7, 121.5/6, 108/5, 81/4, 54/3, 40.5/2, 27/1, 13.5/0Mbps 802.11n 20MHz mode: 65/7, 58.5/6, 52/5, 39/4, 26/3, 19.5/2, 13/1, 6.5/0Mbps

#### Transmission Mode

- IEEE802.11b: CCK (11 Mbps, 5.5 Mbps) DQPSK (2 Mbps) DBPSK (1 Mbps)

- IEEE802.11g: OFDM

- IEEE802.11n: OFDM

#### Modulation System

- IEEE802.11b: DBPSK, DQPSK, CCK

- IEEE802.11g: BPSK, QPSK, 16-QAM, 64-QAM, OFDM

- IEEE802.11n: BPSK, QPSK, 16-QAM, 64-QAM, OFDM

#### Access Method

CSMA/CA

#### Security

- WEP (64bit/128bit)

- WPA-PSK (Personal) / WPA2-PSK (Personal) / WPA-802.1x TKIP, AES

- MAC Address Filtering

- WPS Button Support

#### Correspondence Mode

Infrastructure

#### Antenna Type

1x 1.8dbi external antenna

#### Others

##### Reset Button

- Reset to Factory: Push and hold on 8 seconds
- Reboot: Push and release

### Environmental Condition

- Operating: Temperature 0 ~ 40 °C /Humidity 85% or less (non-condensing)

- Storage: Temperature -20 ~ 60°C /Humidity 95% or less (non-condensing)

- Power United 12V, 1A

### Firmware Specification

#### ATM

- Supports UBR/(CBR/VBR)

- VPI Range (0-255) and VCI range (32-65535)

- Support OAM F4/F5 loopback

- Payload Encapsulation:

- RFC2684, Multi-protocol Encapsulation over AAL5

- RFC2684 (RFC1483/2684), Bridge mode RFC2684, IPoA

- RFC2364, PPP over ATM (CHAP and PAP supported)

- RFC2516, PPPoE (PPP over Ethernet)

- Support auto-detection for VPI/VCI (VPI: 0~10, VCI: 32~90) and multiplexing method (VC-based, LLC-based)

#### Protocol Support

- DHCP client/server for LAN

- SMTP

- NTP (Network Time Protocol)

- DHCP client for WAN

#### Routing

- Cross Segment Static Route

- RIP1, RIP 2

#### Firewall

- NAT

- Attack Alert (Email) and log

- Denial of Service (SPI)

- Access Control

- Port Forwarding

- Port Range Forwarding

- Schedule-based URL Content Filtering

#### VPN pass-through

- PPTP (pass through)

- L2TP (pass through)

- IPSec (Pass through)

#### Management

- Web based configuration

- Remote Management through WAN port

#### UPnP

Universal Plug-and-Play

#### Other Features

- DNS Proxy

- Dynamic DNS (Multiple DDNS including Dynamic DDNS, custom DDNS, TZO,)

- DMZ support

- Dial on demand and auto disconnect

- WDS support

- QoS

#### Firmware Upgrade

HTTP upgrade

## Product Diagram



## Order Information

### Package Content

**WBR-6601:** 150Mbps N Wireless ADSL2+ Modem Router

WBR-6601

LAN Cable

Power Adapter

Quick Installation Guide

CD Manual