



AIRTIES RT-211 125Mbps Wireless ADSL2+ 4 Port Router

- ADSL2 + (24Mbps/4Mbps)
- PSTN and ISDN support (Annex A & Annex B in a single device)
- 125Mbps Wireless G + + Technology
- AirTies Mesh Technology
- Automatic Wireless Setup & Security
- Advanced Security with anti-DoS
 SPI Firewall
- Internet access control through URL, <u>IP or MAC</u> address filtering
- ADSL Usage Monitor
- Universal Plug & Play
- Easy Setup CD (with animated instructions)
- Automatic Firmware Updates
- 4 Ethernet ports
- Splitter included
- 3 year warranty
- 24x7 technical support





Wireless Internet Freedom

ADSL2+ Router, Firewall, 125Mbps G++ Wireless Access Point, 4-Port Switch

AirTies RT-211 125 Mbps Wireless ADSL2+ 4-Port Router is an all-in-one solution for Internet connectivity in your home or office. With the **RT-211**, you can easily set up your wireless network and ADSL connection. Once configured, you can access the Internet over the wireless network from any location in your home or office and share the Internet connection between up to 253 computers.

The RT-211 offers both **Annex A and Annex B support**. With this AirTies patent pending technology, your router works with either traditional PSTN or digital ISDN phone lines and you don't have to worry about which product would be the right one for your ADSL connection type.

AirTies RT-211 supports G++, one of the latest wireless technologies. With G++, you can achieve significantly faster wireless data rates (up to 125Mbps) without sacrificing connection quality or network security. In addition, you can enjoy wider wireless coverage area compared to earlier wireless technologies. To take advantage of the G++ feature, wireless devices in your network need to support this technology as well.

The RT-211 supports AirTies Mesh Technology which resolves wireless problems such as loss of wireless signal or limited coverage area, often encountered in multiple storey, stone or reinforced concrete buildings. With Mesh Technology, all video broadcast and ADSL based/originated IPTV can now be distributed wirelessly within consumer homes no matter the building structure.

The advanced wireless security standards supported by the AirTies RT-211 (WPA, WPA2, WEP and 802.1x) and the anti-DoS SPI Firewall provide you with the highest level of data protection. The firewall also allows URL, IP and MAC-address based Internet access controls.

With the RT-211, you don't need to worry about the details of wireless security setup. The AirTies Utility Program automatically configures your wireless security settings. A wireless network key is created, stored on your router and also entered into your computer automatically. Unless you share your network key with someone else, no one else can access the Internet through your wireless network and put you at risk by unauthorized use.

The **Automatic Firmware Upgrade** feature informs the user when a new firmware version is available and, if the user chooses to, automatically upgrades the router with the new firmware. With the latest firmware on your device, you have the advantage of using the latest technologies and maximizing the performance of your device.

Main Features

- All-in-one solution: ADSL2+ Router, 125Mbps Wireless Access Point, Firewall and 4-port Switch.

- All-In-one solution: ADSL2+ Router, 125Mbps wireless Access Point, Firewall and 4-port Switch.
 ADSL2+ Technology: High speed Internet with 24Mbps download and 4Mbps upload speeds
 Annex A and Annex B support: works with either the traditional PSTN or digital ISDN phone lines
 High speed wireless with G++: 125 Mbps wireless Access Point (when used with other AirTies wireless devices that also support 125Mbps). Also, backward compatible with 802.11b/g.
 Advanced Wireless Security: Latest wireless security technologies that support WPA (Wi-Fi Protected Access), WPA2 (IEEE 802.11i), WEP (Wired Equivalent Privacy) encryption and 802.1x standards
 Maximum Wireless Access range and Mesh Technology: Ranges of up to 400 meters outdoors and 100 meters indoors standard. Evtendible with AirTies Microlagy upice and 100 meters indoors
- standard. Extendible with AirTies Mesh Technology, using additional AirTies wireless access point devices. Automatic Wireless Key Setting: Automatic Wireless Security configuration for the router and the PC using the AirTies
- ADSL Utility

- Advanced Firewall for maximum security: Advanced anti-DoS SPI Firewall; URL, IP and MAC address based filtering, DMZ
 Quick and easy installation with the Easy Setup CD
 Automatic Firmware updates: Automatic firmware update support through the AirTies ADSL Utility
 ADSL Usage Monitor: Especially useful for limited quota ADSL subscribers. Reports monthly total download and upload amounts and current download rate.
 DUCD convert advanced router with NAT, NAPT, DIPut (v2 support)
- DHCP server, advanced router with NAT, NAPT, RIPv1/v2 support
 8 Channel PVC support
 VPN pass-through
- Robust against AC voltage fluctuations: Specially designed to withstand wide voltage fluctuations
- Wired device support: Connect up to 4 wired devices to your local network via the 10/100Mbps Ethernet ports.
- Web based user interface
- 24x7 technical support by a highly trained AirTies support team and backed up by the AirTies R&D team
- 3 year extended warranty

Technical Properties

- ADSL properties: G.992.1 Annex A,B (G.DMT), G.992.2 (G.Lite), G.992.3 (ADSL2), G992.4 (G.Lite.bis), G.992.5 (ADSL2+), Rate Adaptive DSL (RADSL), READSL, Traffic shaping UBR/CBR, OAM (I.610), support for 8 PVCs
 ATM support: PPPoE, PPPoA, RFC1483 Bridging, RFC1483 Routing, Classical IP over ATM, PAP/CHAP, RFC 2364 PPP over AAL5, RFC2366 Multicast over ATM
 802.11b/g and G++ wireless networks: 1, 2, 5.5, 6, 9, 11, 12, 24, 36, 48, 54 Mbps data rates (automatic speed adjustment) and 125 Mbps G++ mode
 Wireless Output, Dewards, 2048m ELIPP

- Wireless Output Power: 20dBm EIRP
- Wireless security options: WPA (802.1x, TKIP, PSK); WPA2 (AES); 64/128/256 bit WEP, wireless MAC address filtering, SSID hiding
- STD hiding
 Frequency interval: ETSI 2400 MHz(min)- 2483.5 MHz(max) (13 channels with 3 not overlapping)
 Router and Firewall: Anti-DoS SPI firewall; URL, IP and MAC address based filtering; Port forwarding; DMZ; VPN pass-through (PPTP, L2TP, IPSec); Static Routing, RIPv1, RIPv2 forwarding; DNS Proxy; DHCP server and client; NAT/NAPT; PPP (PAP/CHAP/MSCHAP); IP multicast IGMP V1&V2 proxy
 Remote Management: SNMP and TR-069
 UPnP : Universal Plug&Play
 Reset button to return the router to default settings
 Operating Voltage Pange: 170V AC to 240V AC

- Operating Voltage Range: 170V AC to 240V AC
 Cabling: RJ-45 (Ethernet), RJ-11 (ADSL)
 LEDs: PWR Power, ADSL ADSL signal , PPP Internet connection, WLAN Wireless network activity, LAN Local network activity
- Compatible with Windows 98, ME, 2000, 2003, XP, Vista, UNIX, Linux, MAC OS Certificates: CE

Physical Characteristics

- Dimensions: 155mm x 125mm x 25mm
- Weight: 450 g
 Power: 12Volt, 1000mA
- Adapter operating voltage: Between 170V and 240V
 Operating Temperature: 0°C 40°C
 Storage Temperature: -40°C 70°C
 Humidity: %10 %90

Minimum System Requirements

- In order to configure your AirTies RT-211 router, you will need a PC with an Ethernet card or wireless network adapter and runs any version of Windows or Unix, Linux, or Mac operating systems.
 Windows 98/ME/2000/XP/Vista for running the AirTies Utility software
- The router does not need to be connected to a PC during normal operation.

Package Contents

- AirTies RT-211 125Mbps Wireless ADSL2+ 4-Port Router
- Power adapter
- Ethernet cable Standard telephone/DSL cable (1 long and 1 short)
- SplitterAirTies Easy Setup CD
- User Manual

E-Mail: info@airties.com | www.airties.com Phone: +90 212.444 0 239 Fax: +90 212.318 62 98 AirTies Wireless Networks

