

ADSL2/2+

4 Ethernet Port | WiFi | USB Device

CT-5361T Wireless Router



The CT-5361T Wireless ADSL2/2+ Router is designed for residential or business applications that require wired and wireless connectivity to a broadband network. It comes fully equipped with four Fast Ethernet ports, a single USB port and integrated 802.11g WLAN Access Point (AP) for wireless connectivity. TR-069 compliance allows for auto configuration and control via remote server (ACS), while state of the art security is achieved with WPA data encryption, Firewall and VPN with pass through (PPTP/L2TP/IPSec).

FEATURES

Wireless LAN Connections (with WPS)

An integrated 802.11b/g Access Point (AP) supports LAN traffic at speeds of up to 54 Mbps. The Wireless Protected Setup (WPS) feature makes wireless connection setup quick and secure.

Fast Wired Connections (up to 100 Mbps)

The ADSL2/2+ port carries WAN traffic at speeds of up to 24 Mbps (ADSL2+), while five Ethernet ports support LAN traffic at speeds up to 100 Mbps. The TR-068 compliant rear panel and LED indicators also simplify installation and improve ease-of-use.

Safe & Secure Connections

First, both a Stateful Firewall (with DoS protection) and NAT/PAT protect the LAN from external threats. Second, IP and MAC address filtering provide fine-grained access control to or from the network. Third, Virtual Private Networks (VPN) with pass-through (PPTP/L2TP/IPSec) and WPA/802.1x/WEP guarantee rock-solid security for both wired and wireless connections.

Quality Of Service

Classify, control, and prioritize diverse traffic types, for pristine video, toll-quality voice, and error-free data.

Remote Management (TR-069 supported)

TR-069/TR-098/TR-111 standards compatibility ensures interoperability with central office remote management equipment. From the user perspective this reduces downtime and frustration. For the service provider it means improved customer relations and cost savings. Other management options include telnet, ssh and a web user interface with advanced functionality.

Reliable Quality Products

For over 20 years Comtrend has delivered superior quality products to our customers worldwide. Every product goes through rigorous testing, and is backed by a 2 year warranty.

CT-5361T

4 Ethernet Port | WiFi | USB Device



SPECIFICATIONS

Hardware

- RJ-11 X1 for ADSL,
- RJ-45 X 4 for LAN,
- USB X1 for LAN,
- Reset Button X 1,
- Power switch X 1,
- WiFi Antenna X1

WAN

- Comply with ITU-T G.992.5, ITU-T G.992.3, ITU-T G.992.1, ANSI T1.413 Issue 2
- G.992.5 (ADSL2+):
Downstream : 24 Mbps Upstream : 1.3 Mbps
- G.992.3 (ADSL2)
Downstream : 12 Mbps Upstream : 1.3 Mbps
- G.DMT
Downstream : 8Mbps Upstream : 832kbps
- AnnexM

LAN

- IEEE 802.3, IEEE 802.3u
- 10/100 BaseT auto-sense
- Support MDI/MDX

Wireless

- IEEE802.11b/g
- 64, 128-bit Wired Equivalent Privacy (WEP) Data Encryption
- 11 Channels (US, Canada)/ 13 Channels (Europe)/ 14 Channels (Japan)
- Up to 54Mbps data rate
- MAC address filtering, WDS, WEP, WPA, WPA2, IEEE 802.1x
- 10,25,50,100mW@22MHz channel bandwidth output power level can be selected according to the environment

ATM Attributes

- RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Route; RFC 2516 (PPPoE); RFC 1577 (IPoA)
- Support up to 16 PVCs
- AAL5
- UBR/CBR/VBR-rt/VBR-nrt
- UNI 3.1/4.0
- OAM F4/F5

Management

- TR-069/TR-098/TR-104/TR-111, SNMP, Telnet, Web-based management, Configuration backup and restoration
- Software upgrade via HTTP, TFTP server, or FTP server

Security Functions

- PAP, CHAP,
- Packet and MAC address filtering,
- Access control and SSH
- Four level login including local admin, local user and remote technical support access and apuser for WiFi access

Power Supply

- 120 Vac, 16.5Vdc/850mA

Networking Protocols

- RFC2684 VC-MUX, LLC/SNAP encapsulations for bridged or routed packet
- RFC2364 PPP over AAL5
- IPoA, PPPoA, PPPoE, Multiple PPPoE sessions on single PVC, PPPoE pass-through, PPPoE filtering of on-PPPoE packets between WAN and LAN
- Transparent bridging between all LAN and WAN interfaces
- 802.1p/802.1q VLAN support
- Spanning Tree Algorithm
- IGMP Proxy V1/V2/V3, IGMP Snooping V1/V2/V3, Fast leave
- Static route, RIP v1/v2,
- DHCP Server/Client/Relay,
- DNS Relay, Dynamic DNS,
- ARP, RARP

QoS

- Packet level QoS classification rules,
- priority queuing using ATM TX queues,
- IP TOS/Precedence,
- 802.1p marking,
- DiffServ DSCP marking
- src/dest MAC addresses classification.

Firewall/Filtering

- Stateful Inspection Firewall
- Stateless Packet Filter
- Day-time Parental Control
- Denial of Service (DOS): ARP attacks, Ping attacks, Ping of Death, LAND,SYN, Smurf, Unreachable, Teardrop
- TCP/IP/Port/interface filtering rules Support both incoming and outgoing filtering

NAT/NAPT

- Support Port Triggering and Port forwarding
- Symmetric port-overloading NAT, Full-Cone NAT
- Dynamic NAPT (NAPT N-to-1)
- Support DMZ host
- Virtual Server
- VPN Passthrough (PPTP, L2TP, IPSec)

Application Layer Gateway (ALG)

- SIP, H.323, Yahoo messenger, ICQ, RealPlayer, Net2Phone, NetMeeting, MSN, X-box, Microsoft DirectX games and etc

Environment Condition

- Operating temperature: 0 ~ 50 degrees Celsius
- Relative humidity: 5 ~ 95% (non-condensing)

Dimensions

205mm(W) X 48mm(H) X 145mm(D)

Kit Weight

1*CT-5361T, 1*RJ11 cable, 1*RJ45 cable, 1*power adapter, 1*CD-ROM = 1 kg

Note: Specifications are subject to change without notice



COMTREND CORPORATION



Taiwan:
3F-1, No.10, Lane 609, Chung Hsin Road Section 5, San Chung, Taipei, Taiwan 24159
Tel: 886-2-2999-8261
Fax: 886-2-2999-8497

China:
NO.88 East QianJin Road,Kunshan City,JiangSu,China
Tel: 86-512-57383156, 86-512-57383157,
86-512-57384515
Fax: 86-512-57383155

Spain:
Edif. América II C/Prócion,7 portal 3 bajo H 28023 Madrid, Spain
Tel: 34-917990403
Fax: 34-913510999

UK:
566 Chiswick High Road Building 3, Chiswick Park Chiswick - London, W4 5YA UK
Tel: 44-0-8453701031
Fax: 44-0-8453701032

France:
87, Rue du Gouverneur Général Félix Eboué 92130 Issy-les-Moulineaux, France
Tel: 33-1-70715700
Fax: 33-1-70715701

Czech Republic:
TOKOVO Jankovcova 1518/2, 170 00, Prague 7, Czech Republic
Tel: 420-266-782040
Fax: 420-266-782990

USA & Canada:
16 Goodyear, Suite 120, Irvine, CA 92618
Tel: 1-949-7539640
Fax: 1-949-7539020

Brazil:
Al. Campinas, 977 - 7º. Floor - Room 71 / 72 - Jardins
Zip Code: 01404-001 - São Paulo - SP - Brazil
Tel: 00 55 11 3052-2295
Fax: 00 55 11 3052-2295

Mexico:
Mariano Escobedo 396 Office 503 Colonia Anzures, Deleg. Miguel Hidalgo 11590 Distrito Federal México
Tel: +52 (55) 4623-1516