

16/32-Port VoIP Station Gateway

High Port Density Gateway for Business

- 16 or 32 FXS Internet Phone Ports
- DSL/Cable Modem Broadband Connection
- Voice Compression Format to Save Internet Bandwidth
- Real-Time/Toll-Quality Voice
- High Port Densities to Save Cost/Maintenance

FEATURES

Internet Telephone

- High Density of 16 or 32 FXS Ports
- Ideal for Business Phones/Fax Connection
- Compatible With SIP Services
- Extensive Call Feature Support
- Guaranteed Toll-Quality Voice Even in Busy Network

Call Features

- Call Hold, Wait, Forward, Transfer
- Easy Tracking With Call Detailed Records
- Greeting Message, Caller ID Delivery

WAN/LAN Connection

- 10/100Mbps Ethernet WAN Port
- 10/100Mbps Ethernet LAN Port
- WAN Connection Supports PPPoE, DHCP Client, DDNS

Configuration/Upgrade

- Easy Configuration by IVR or Web-Based GUI
- Web-Based Firmware Upgrade

The DVG-2016S/DVG-2032S VoIP station gateways present an ideal Internet telephone solution for business use. These gateways convert voice traffic into data packets for transmission over the Internet, combine the industry's latest Voice over the IP network technology with advanced communication features, and are fully compatible with SIP Internet phone services. With high port densities, they provide a low cost of ownership, convenience and great savings for companies needing to place frequent long-distance and international business calls.

Cost Saving and Investment Protection. The DVG-2016S/DVG-2032S gateways provide businesses with an easy and inexpensive upgrade to Internet telephony while allowing them to retain their existing telephone and fax equipment. These devices allow businesses to protect and extend their past investments in telephones, conference speakers phones and fax machines, as well as to control their migration to IP with a very affordable and incremental investment.

16 or 32 Internet Telephone Connections. Each gateway provides 16 or 32 FXS ports for simultaneous Internet phone connections. Plug in regular phone sets to these ports, and they instantly become Internet telephones. For businesses with frequent needs for long-distance and international phone calls, these devices provide great cost savings and convenience, while keeping configuration and maintenance to a minimal level.

Guaranteed Voice Quality. The DVG-2016S/DVG-2032S gateways deliver clear voice and reliable phone/fax communication through implementation of internationally recognized standards for voice and data networking. They incorporate Quality of Service (QoS) functions to ensure that voice received through the Internet is the same as or even surpasses that received on the ordinary phone.

Convenient Call Features. The DVG-2016S/DVG-2032S gateways support extensive call features, allowing the service providers to offer these functions to their subscribers. Provided that the telephone sets at the end-users side support these functions, callers can take advantage of these convenient features. Configuration of individual phone connection is easy using the multi-language Interactive Voice Response (IVR) or the web-based user's interface.



▪ DVG-2016S
16-Port Gateway



▪ DVG-2032S
32-Port Gateway

Technical Specifications

Device Interfaces

- 16 FXS ports in 1 RJ-21 connector (DVG-2016S)
- 32 FXS ports in 2 RJ-21 connectors (DVG-2032S)
- 10/100BASE-TX RJ-45 WAN port
- 10/100BASE-TX RJ-45 LAN port

WAN Access Types

- DHCP client
- PPPoE client
- Static IP address
- PPTP
- BigPond Cable (Australia)
- MAC cloning on WAN port

Phone Book

- Phone Book Manager Server (selected version), up to 200 IAD registrations
- Phone Book Manager Client

QoS

- SIP and RTP always first policy
- WAN access rate control
- IP Precedence, DSCP (DiffServ) tagging on SIP and RTP packets
- LAN port rate limit, hi/low queue control

SIP

- By port registration
- By IAD registration
- Mixed configuration of "By Port" and "By IAD" on the same IAD
- Outbound Proxy
- Session Timer: Update, Re-Invite
- E.164 Numbering
- Redundant SIP PROXY support (fail-over by registration)
- SIP PING (on special version)
- Adjustable NAT port binding interval (binding with Proxy)

- CLIR (anonymous caller ID)
- Hot line/warm line
- Group hunting, configurable hunting sequence
- Support one-way media (SIP 183)
- Call hold
- Call waiting
- Call transfer: attended, unattended
- Call forward: unconditional, busy, no answer
- 3-way conference compatible with NORTEL MCS5200
- T.30 fax pass-through
- T.38 fax relay
- Adjustable fax tone detection level
- Out-of-band DTMF: RFC2833, SIP INFO

Telephony Features

- G.711 a/u, G.726 (32K), G.729A, G.723.1
- Adjustable jitter buffer
- Adjustable packet time (by Codec type)
- Silence detection and suppression
- Echo cancellation
- Digit map defines number length by leading digits, route assignable
- Local phone book enables calling to other VoIP devices without registration
- Speed dial
- Caller filter accept/deny caller by IP address
- On machine user-recorded prompt message
- FXS caller ID generation: DTMF, FSK (Bell core/ETSI)
- End of digit tone (inform user complete codes accepted)
- Configurable dial-way timeout/inter-digit timeout/DTMF on-off length
- Adjustable listening & speaking volume (-6 to +6db)
- Adjustable tone volume (1 to 5)
- Adjustable FLASH time

Management

- Web-based & Telnet
- By Provision Server
- 2 privilege WEB login accounts
- 3 web languages by default (English, traditional Chinese, simplified Chinese)
- System information shows device status and registration status
- Per call RTP packet summary
- PING test
- STUN inquiry

LED Indicators

- Power
- Reset
- Alarm
- Run
- 1 to 16 (DVG-2016S)
- 1 to 32 (DVG-2032S)

Physical & Environmental

Power Input

- 90 to 260 VAC, 50/60Hz internal universal power supply

Dimensions

- 442 x 330 x 43 mm
- 19-inch standard rack-mount width, 1U height

Weight

- DVG-2016S: 4.1 kg
- DVG-2032S: 4.4 kg

Operating Temperature

0° to 45°C

Storage Temperature

-25° to 75°C

Humidity

Up to 95% non-condensing

EMI

- FCC Class A
- CE

Safety

- UL



LISTED
ITE
E141136
66F9

D-Link Worldwide Offices

U.S.A.	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Europe (U. K.)	TEL: 44-20-8955-9000	FAX: 44-20-8955-9001	Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
France	TEL: 33-1-30238688	FAX: 33-1-30238689	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	India	TEL: 91-022-26526696	FAX: 91-022-26528914
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Turkey	TEL: 90-312-473-40-55	FAX: 90-312-473-40-58
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	Egypt	TEL: 202-291-9035	FAX: 202-291-9051
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Norway	TEL: 47-99-300-100	FAX: 47-22-309580	LatinAmerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081	Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Portugal	TEL: 351-21-8688493		Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099 #350
Czech Republic	TEL: 420-(603)-276-589	FAX: 41(0)-1-832-11-01	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 30-210-9916902	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Greece	TEL: 30-210-9914 512		Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-8168
			Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898