



BR-6314K

Fast Ethernet Broadband Router



Complete standard features

BR-6314K is a full-featured broadband router that establishes with connection to local area network or individual PC with build-in 4-port Switch. It uses advanced WavePlus broadband router solution provides complete set of industry standard features (PPPoE/Static IP/DHCP/L2TP/PPTP/Telstra Big Pond) for high-speed Internet access. It also offers easy installation and cost-effective connection for corporate, SOHO and residential users.

EZmax Multi-languages Setup Wizard*

A unique 16-language setup wizard is included in the CD ROM. You can select your native language and follow the simple steps to setup Internet connection, password and firmware upgrade.

High Throughput

BR-6314K built-in hardware-based NAT function to decrease CPU loading. The hardware NAT can provide you high performance throughput to access Internet application quickly.

Virtual Server and DMZ

For application that demand open port such as network gaming and web server, the Virtual Server and DMZ functions will provide the ideal solution.

Internet Connection Sharing

Integrated 4-port Ethernet switch, BR-6314K is able to maximize Cable or xDSL Internet connection. With the built-in DHCP server and NAT function, it allows up to 253 devices share the Internet connection at the same time.



FEATURES AND TECHNICAL SPECIFICATIONS

HARDWARE INTERFACE	MANAGEMENT	POWER ADAPTER
<ul style="list-style-type: none"> 1 RJ-45 WAN Port 4 RJ-45 Ethernet LAN Ports LED Indicators: Power, WAN, LNK/ACT,10/100M Reset Button 	<ul style="list-style-type: none"> Supports Remote Management System Status and Log (Web Interface) Firmware Upgradeable 	<ul style="list-style-type: none"> DC 9V, 0.5A
WAN	INSTALLATION	MEMORY
<ul style="list-style-type: none"> Supports cable/xDSL modem WAN Protocols: PPPoE/Static IP/DHCP/L2TP/PPTP/Telstra Big Pond 	<ul style="list-style-type: none"> 16-languages EZmax Setup Wizard 	<ul style="list-style-type: none"> 2 MB NOR Flash 16 MB SDRAM
SECURITY	TEMPERATURE	HUMIDITY
<ul style="list-style-type: none"> NAT / NAT IP Sharing ACL, MAC / IP Filter and URL blocking Virtual Server and Virtual DMZ 	<ul style="list-style-type: none"> 0~40 Degree Celsius 0~70 Degree Celsius (Storage) 	<ul style="list-style-type: none"> 5-95% (Non-condensing)
FUNCTIONS	DIMENSION	CERTIFICATIONS
<ul style="list-style-type: none"> Static Routing RIP version 1 (RFC 1058) and version 2 (RFC 1723) NAT NAPT DHCP Server/Client 	<ul style="list-style-type: none"> 125 x 85 x 25 mm 	<ul style="list-style-type: none"> CE, FCC

NETWORK SETUP DIAGRAM AND RELATED PRODUCTS

An example of how the BR-6314K can be setup:

- Connect the BR-6314K router to your Ethernet (RJ-45) cable/xDSL modem.
- Connect a computer to the LAN port and setup the Internet connection by running the multi-language setup wizard.
- Share the Internet connection by connecting a LAN cable to other devices.
- You can also share your printer using an Edimax print server.

