1 Link Pro SOHORowter

SOHORouter 402VE 4-Port 10/100 Switch VPN Broadband Router w/2*WAN port



Introduction

BR-402VE is a SOHO router that provides an easy and facility way to quickly connect an entire network to Internet. Using the VPN router, a secure connection may be easily created between two or more sites. Whenever data is intended for the remote site, VPN router automatically encrypts the data and sends it to the remote site over Internet, where it is automatically decrypted and forwarded to the intended destination. Connecting to ADSL or Cable through its WAN Ethernet port, BR-402VE can support a bandwidth of 100 Mbps which is 1790 times faster than a 56K modem. The BR-402VE also has one WAN asynchronous port that can be used as a dialup backup to the ADSL/Cable connection. The BR-402VE supports DHCP, Hacker Logging, VPN, firewall and many other functions that are essential for an enterprise daily operation.

Key Features & Benefits

ey reatures & benefits	
Security	 Support up to 32 IPSec tunnels for office to office and/or remote client IPSec connections Support IKE pre-shared key & manual key exchange. Support versatile data encryption algorithms: DES & 3DES (by hardware encryption engine), AES. Support MD5 & SHA-1 key hash authentication algorithms
PPTP Client	Support both PPTP client functions.
Aggressive Mode	 Allow users to configure IKE pre-shared key as RADIUS tunnel attributes for IPSec peers.
Stateful Packet Inspection	Ensuring maximum security
IP Sharing (NAPT)	Share Internet access with single IP address for up to 253 users
DMZ (De-militarized Zone)	Allow one local user to be exposed to the Internet
Virtual Server	 Allow internal servers/workstations to be accessible from Internet.
Firewall	 Guarantee network security and prevent unauthorized users from entering internal local network. Filtering: filter-out un-permitted inbound (WAN)/outbound (LAN) Internet access by IP address, port number, packet type and MAC address. URL blocking: prevent users to access to specific Web sits on Internet.
Hacker Attack & Intruder Detection	 Support general hacker attack pattern monitoring and logging, as well as general DoS (Denial of Service) event filtering. Provide possible occurred hacker attacks information (date/time, source IP, destination IP, protocol, event).
DoS Attack Alerting	• Support real time DoS attack alert and periodical security event log sent through e-mail.
DHCP Server/Client	 Support both DHCP Client & Server that automatically assign/acquire IP addresses to/from network users/ISP. Support DHCP log to show current DHCP clients information.
PPPoE Client	 Support PPPoE client function to connect to PPPoE server.
DDNS (Dynamic DNS)	Allow dynamic public IP address to be located by a host or domain name.
FQDN (Fully Qualified	Allow users to specify static FQDN to IP address mapping in IPSec
Domain Name)	function.
UPnP	 Support Microsoft Universal Plug & Play (UPnP) standard.
Dial Backup	Support dial backup function in case broadband connection fails.
Dial-on-Demand	Eliminate the needs of dial-up and automatically login to your ISP



1 Link Pro SOHORowter

Key Features & Benefits

Idle Timer	•	Let users set a specified idle time before automatically disconnecting
		Internet connection
System Administration	•	Allow network manager to remotely monitor and/or configure this device with password protection.
System Diagnostic	•	Support system diagnostic tool for easy troubleshooting
Web-Based Management	•	Easy installation and configuration with any standard browser.

Specifications

pecifications	
Hardware	High performance ARM-9 class RISC CPU
	16M bytes SDRAM and 1M bytes Flash Memory
	Asynchronous RS-232 port (230 Kbps) x 1
Network Interfaces	Ethernet WAN port (10/100 Base-T) x 1, auto crossover
	 Ethernet LAN 4-port 10/100 Base-T switch, auto crossover
	IPSec tunneling & pass-through
	PPTP server/client & pass-through
	L2TP pass-through
	IP Authentication Header (AH)
	IKE "pre-shared key" and "manual key" exchange
VPN	IKE "main mode" and "aggressive mode"
	MD5 and SHA-1 authentication
	IP Encapsulating Security Payload (ESP)
	Internet IP Security Domain of Interpretation for ISAKMP
	Internet Security Association and Key Management Protocol
	(ISAKMP)
Security	DES, 3DES
	• AES
	PAP, CHAP, MS-CHAP (for RS-232 dial-backup)
	MAC address control
	Prevention of DoS (Denial of Service)
	Stateful Packet Inspection (SPI)
Firewall	Hacker Attack Logging
	DoS Attack Alerting
	NAT natural
	• DMZ
	Filtering
	Virtual Server
	Access Control
	URL Blocking
Protocols & Standards	WDS; TCP/IP; DHCP client/server; PPPoE; PPP; RIP 1/2, static route;
	ICMP; ARP; NAPT; DDNS; FQDN; UPnP; HTTP; SMTP; PING
Power Supply	• DC 12V, 1.2A
LED Indicators	Power, Status, WAN, Serial, LAN 1, 2, 3, 4

Ordering Information:

BR-402VE: 4-Port 10/100 Switch VPN Broadband Router w/2*WAN port

^{*} Product specification subject to change without notice.

