

PROLINK®

www.prolink2u.com

Your Inspirations.
Our Innovations.

PRN3005L 4G LTE Wireless-N Router



The **PROLINK® PRN3005L** is a 4G LTE Wireless Router that lets you access and share a high-speed 4G LTE network of up to 150Mbps simply by inserting your 4G SIM card to the device.

With 2T2R MIMO Wireless technology, the **PROLINK® PRN3005L** can handle wireless data speeds of up to 300Mbps, ensuring multiple Wi-Fi devices get the fastest and best internet access experience.



4G Data Connection

- Share the 4G LTE network with multiple Wi-Fi devices and enjoy faster download speeds of up to 150Mbps.



Automatic Network Selection (Auto-APN)

- Just insert a SIM card, and it will connect to GPRS/EDGE/HSPA/HSPA+/LTE networks automatically without any configuration.



300Mbps High-Speed Wireless

- 2T2R MIMO Wireless Technology delivers greater throughput and performance. Ideal for video streaming, online gaming and internet surfing.



Simple & Easy Setup

- Supports WPS configuration via a 1-push button.

Secured Network

- Advanced WPA-PSK / WPA2-PSK encryption protects your network from security threats.



SMS#

- Enable the use of 3G or 2G network for sending text messages.

Depends on the subscription plan of respective SIM card. SMS charges are applicable.

Specifications

Wi-Fi	<ul style="list-style-type: none">• 2.400 - 2.4835GHz Frequency Band• IEEE802.11b/g/n• WPS supported• WiFi Distance of up to 100m
Receiver Band	<ul style="list-style-type: none">• LTE FDD (optional): 1800MHz (Band 3)• LTE TDD: 2600MHz (Band 38)
Data Rate	<ul style="list-style-type: none">• LTE FDD (Cat4): DL 150Mbps, UL 50Mbps
Antenna	<ul style="list-style-type: none">• Wi-Fi Internal Antennas: up to 3dBi• LTE Internal Antennas: up to 5dBi; SMA connectors available for external antennas
Interface	<ul style="list-style-type: none">• 8 x LED indicators• DC Jack (12V)• WPS button• Reset button• SIM card slot• Power on/off• 2 X RJ45 port• 2 X RJ11 port
LED	<ul style="list-style-type: none">• Power, WiFi, Internet, LAN1, LAN2, 3 Signal LEDs
Power Adapter	<ul style="list-style-type: none">• Input: 100~240V, 50Hz~60Hz• Output: 12VDC / 1A
Output Power	<ul style="list-style-type: none">• Max 20dBm (Wi-Fi); Max 23dBm (LTE)
Voice	<ul style="list-style-type: none">• SIP VoIP/VoLTE supported
Environment	<ul style="list-style-type: none">• Operating Temperature: 0 to 45°C• Storage Temperature: -20 to 70°C• Operating Humidity: 10% ~ 95%• Storage Humidity: 5% ~ 95%
Dimensions	<ul style="list-style-type: none">• 140 x 122 x 25mm (L x W x H)
Weight	<ul style="list-style-type: none">• ~200g



Check 3G/4G network frequency compatibility for PROLiNK® PRN3005L in any country and mobile network carrier: <http://prolink2u.com/check4g/>

Authorised Distributor/ Reseller:



Compatible with:



System Requirements:

Windows XP/Vista/7/8/10, Mac*
*Support for Intel-based Mac only

PROLiNK® is a trademark of Fida International (S) Pte Ltd and is manufactured under its authority. Microsoft®, Windows®, Windows® 98SE/ME/2000/XP/Vista/7/8/10 are either registered trademarks or trademarks of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple, Inc., registered in the U.S. and other countries. Linux® is a registered trademark of Linus Torvalds and Linux penguin "Tux" created by Larry Ewing and The Gimp. All other brands, products, services, logos and company names mentioned herein are trademarks of their respective owners.

All specifications, designs and contents are subjected to changes without prior notice. Images are for demonstration and may vary from actual products. © Copyright 2017. PROLiNK® All rights reserved.

