D-Link AirPlus XtremeG[™] DI-624 High-Speed 2.4 GHz Wireless Router

Manual



Contents

Package Contents	3
Introduction	4
Wireless Basics	8
Getting Started	12
Using the Configuration Menu	14
Networking Basics	41
Troubleshooting	70
Technical Specifications	77
Contacting Technical Support	80
Warranty and Registration	81

Package Contents

Contents of Package:

D-Link AirPlusXTREME G DI-624 High-Speed 2.4GHz Wireless Router

D-Link

- Power Adapter-DC 5V, 3.0A
- Manual and Warranty on CD
- Quick Installation Guide
- Ethernet Cable

Note: Using a power supply with a different voltage rating than the one included with the DI-624 will cause damage and void the warranty for this product.

If any of the above items are missing, please contact your reseller.

System Requirements for Configuration:

- Ethernet-Based Cable or DSL Modem
- Computers with Windows, Macintosh, or Linux-based operating systems with an installed Ethernet adapter
- Internet Explorer Version 6.0 or Netscape Navigator Version 6.0 and Above

Introduction

The D-Link *Air*PlusXtreme*G* DI-624 High-Speed Wireless Router is a draft 802.11g highperformance, wireless router that supports high-speed wireless networking at home, at work or in public places.


Unlike most routers, the DI-624 provides data transfers at up to 54 Mbps (compared to the standard 11 Mbps) when used with other D-Link *Air*PlusXtreme*G* products. The 802.11g standard is backwards compatible with 802.11b products. This means that you do not need to change your entire network to maintain connectivity. You may sacrifice some of 802.11g's speed when you mix 802.11b and 802.11g devices, but you will not lose the ability to communicate when you incorporate the 802.11g standard into your 802.11b network. You may choose to slowly change your network by gradually replacing the 802.11b devices with 802.11g devices.

In addition to offering faster data transfer speeds when used with other 802.11g products, the DI-624 has the newest, strongest, most advanced security features available today. When used with other 802.11g WPA (WiFi Protected Access) and 802.1x compatible products in a network with a radius server, the security features include:


- WPA*: A new security feature, Wi-Fi Protected Access authorizes and identifies users based on a secret key that changes automatically at a regular interval.
 WPA uses TKIP (Temporal Key Integrity Protocol) to change the temporal key every 10,000 packets (a packet is a kind of message transmitted over a network.) This insures much greater security than the standard WEP security. (By contrast, the older WEP encryption required the keys to be changed manually.)
- **802.1x:** Authentication is a first line of defense against intrusion. In the Authentication process the server verifies the identity of the client attempting to connect to the network. Unfamiliar clients would be denied access.

For home users that will not incorporate a RADIUS server in their network, the security for the DI-624, used in conjunction with other 802.11g products, will still be much stronger than ever before. Utilizing the **Pre Shared Key mode** of WPA, the DI-624 will obtain a new security key every time it connects to the 802.11g network. You only need to input your encryption information once in the configuration menu. No longer will you have to manually input a new WEP key frequently to ensure security, with the DI-624, you will automatically receive a new key every time you connect, vastly increasing the safety of your communications.

Connections







Features

- Fully compatible with the 802.11g standard to provide a wireless data rate of up to 54Mbps
- Backwards compatible with the 802.11b standard to provide a wireless data rate of up to 11Mbps
- **WPA*** (Wi Fi Protected Access) authorizes and identifies users based on a secret key that changes automatically at a regular interval, for example:
 - TKIP (Temporal Key Integrity Protocol), in conjunction with a RADIUS server, changes the temporal key every 10,000 packets, ensuring greater security
 - Pre Shared Key mode means that the home user, without a RADIUS server, will obtain a new security key every time the he or she connects to the network, vastly improving the safety of communications on the network.
- 802.1x Authentication in conjunction with the radius server verifies the identity of would be clients
- Utilizes OFDM technology (Orthogonal Frequency Division Multiplexing)
- User-friendly configuration and diagnostic utilities
- Operates in the 2.4GHz frequency range
- Connects multiple computers to a Broadband (Cable or DSL) modem to share the Internet connection
- Advanced Firewall features
 - Supports NAT with VPN pass-through, providing added security
 - MAC Filtering
 - IP Filtering
 - URL Filtering
 - Domain Blocking
 - Scheduling
- DHCP server supported enables all networked computers to automatically receive IP addresses
- Web-based interface for Managing and Configuring
- Access Control to manage users on the network
- Supports special applications that require multiple connections
 - Equipped with 4 10/100 Ethernet ports, 1 WAN port, Auto MDI/MDIX

Wireless Basics

D-Link wireless products are based on industry standards to provide easy-touse and compatible high-speed wireless connectivity within your home, business or wherever a wireless network is available. D-Link wireless products will allow you access to the data you want, when and where you want it. You will be able to enjoy the freedom that wireless networking brings.

A wireless local area network (WLAN) is a cellular computer network that transmits and receives data with radio signals instead of wires. WLANs are used increasingly in both home and office environments, and public areas such as airports, coffee shops and universities. Innovative ways to utilize WLAN technology are helping people to work and communicate more efficiently. Increased mobility and the absence of cabling and other fixed infrastructure have proven to be beneficial for many users.

Wireless users can use the same applications they use on a wired network. Wireless adapter cards used on laptop and desktop systems support the same protocols as Ethernet adapter cards.

Under many circumstances, it may be desirable for mobile network devices to link to a conventional Ethernet LAN in order to use servers, printers or an Internet connection supplied through the wired LAN. A Wireless Router is a device that can be used to provide this link.

Wireless Basics (continued)

People use WLAN technology for many different purposes:

Mobility - Productivity increases when people have access to data in any location within the operating range of the WLAN. Management decisions based on real-time information can significantly improve worker efficiency.

Low Implementation Costs – WLANs are easy to set up, manage, change and relocate. Networks that frequently change, both physically and logically, can benefit from a WLAN's ease of implementation. WLANs can operate in locations where installation of wiring may be impractical.

Installation and Network Expansion - Installing a WLAN system can be fast and easy and can eliminate the need to pull cable through walls and ceilings. Wireless technology allows the network to go where wires cannot go-even outside the home or office.

Scalability – WLANs can be configured in a variety of ways to meet the needs of specific applications and installations. Configurations are easily changed and range from peer-to-peer networks suitable for a small number of users to larger infrastructure networks to accommodate hundreds or thousands of users, depending on the number of wireless devices deployed.

Inexpensive solution– Wireless network devices are as competitively priced as conventional Ethernet network devices.

The DI-624 is compatible with the following wireless products:

- D-Link Air DWL-650, D-Link AirPlus DWL-650+, D-Link AirPlus XtremeG DWL-G650
 Wireless Cardbus Adapters used with laptop computers
- D-Link Air DWL-520 and D-Link AirPlus DWL-520+, D-Link AirPlus XtremeG DWL-G520
 Wireless PCI cards used with desktop computers
- D-Link AirPlus DWL-900AP+ and DWL-2000AP+ Enhanced 2.4GHz Wireless Access Points
- D-Link AirPlus DWL-800AP+
 Enhanced 2.4GHz Wireless Range Extender
- D-Link AirPlus DWL-810+
 Enhanced 2.4GHz Ethernet-to-Wireless Bridge

Standards-Based Technology

The DI-624 Wireless Broadband Router utilizes the new 802.11g standard.¹

The IEEE **802.11g** standard is an extension of the 802.11b standard. It increases the data rate up to 54 Mbps within the 2.4GHz band, utilizing **OFDM technology.**

This means that in most environments, within the specified range of this device, you will be able to transfer large files quickly or even watch a movie in MPEG format over your network without noticeable delays. This technology works by transmitting high-speed digital data over a radio wave utilizing **OFDM** (**O**rthogonal **F**requency **D**ivision **M**ultiplexing) technology. **OFDM** works by splitting the radio signal into multiple smaller sub-signals that are then transmitted simultaneously at different frequencies to the receiver. **OFDM** reduces the amount of **crosstalk** (interference) in signal transmissions. The D-Link *DWL-G650* will automatically sense the best possible connection speed to ensure the greatest speed and range possible.

802.11g offers the most advanced network security features available today, including: WPA², 802.1x, TKIP, AES and Pre-Shared Key mode. These security features are explained in more detail in the *Introduction* and the *Features* section of this manual.

The DI-624 is backwards compatible with 802.11b devices. This means that if you have an existing 802.11b network, the devices in that network will be compatible with 802.11g devices at speeds of up to 11Mbps in the 2.4GHz range. Also based on the IEEE **802.11b** standard, the DI-624 is interoperable with existing compatible 2.4GHz wireless technology with data transfer speeds of up to 11Mbps.

^{1 802.11}g standard is scheduled for ratification by IEEE Q3 2003

Wireless Basics (continued)

Installation Considerations

The D-Link *Air*Plus *X*treme*G* DI-624 lets you access your network, using a wireless connection, from virtually anywhere within its operating range. Keep in mind, however, that the number, thickness and location of walls, ceilings, or other objects that the wireless signals must pass through, may limit the range. Typical ranges vary depending on the types of materials and background RF (radio frequency) noise in your home or business. The key to maximizing wireless range is to follow these basic guidelines:

- Keep the number of walls and ceilings between the DI-624 and your receiving device (e.g., the DWL-G650 or the DWL-650+) to a minimum each wall or ceiling can reduce your D-Link *Air*Plus Wireless product's range from 3-90 feet (1-30 meters.) Position your receiving devices so that the number of walls or ceilings is minimized.
- 2. Be aware of the direct line between routers and computers. A wall that is 1.5 feet thick (.5 meters), at a 45-degree angle appears to be almost 3 feet (1 meter) thick. At a 2-degree angle it looks over 42 feet (14 meters) thick! Position devices so that the signal will travel straight through a wall or ceiling (instead of at an angle) for better reception.
- 3. Building Materials can impede the wireless signal a solid metal door or aluminum studs may have a negative effect on range. Try to position wireless devices and computers with wireless adapters so that the signal passes through drywall or open doorways and not other materials.
- 4. Keep your product away (at least 3-6 feet or 1-2 meters) from electrical devices or appliances that generate RF noise.

Getting Started


There are basically two modes of networking:

- Infrastructure using an Access Point, or Wireless Router, such as the DI-624.
- Ad-Hoc directly connecting to another computer, for peer-topeer communication, using wireless network adapters on each computer, such as two or more DWL-G650 wireless network Cardbus adapters.

On the following pages we will show you an example of an **Infrastructure Network** and an **Ad-Hoc Network**.

An **Infrastructure** network contains an Access Point or a Wireless Router. The **Infrastructure Network** example shown on the following page contains the following D-Link network devices (your existing network may be comprised of other devices):

- A wireless Router **D-Link** *Air***Plus DI-624**
- A laptop computer with a wireless adapter -D-Link AirPro DWL-G650
- A desktop computer with a wireless adapter D-Link AirPlusXtremeG DWL-G520, D-Link Air DWL-520, or D-Link AirPlus DWL-520+
 (D-Link Air devices have speeds up to 11Mbps)
- A Cable modem D-Link DCM-200



Please remember that **D-Link AirXtremeG** wireless devices are pre-configured to connect together, right out of the box, with their default settings.

For a typical wireless setup at home (as shown above), please do the following:



You will need broadband Internet access (a Cable or DSL-subscriber line into your home or office)



Consult with your Cable or DSL provider for proper installation of the modem



Connect the Cable or DSL modem to the DI-624 Wireless Broadband Router (see the printed Quick Installation Guide included with your router.)



If you are connecting a desktop computer to your network, install the D-Link *Air*Plus *XtremeG* DWL-G520 wireless PCI adapter into an available PCI slot on your desktop computer. You may also install the DWL-520+, or the DWL-520. (See the printed Quick Installation Guide included with the network adapter.)



Install the drivers for the D-Link DWL-G650 wireless Cardbus adapter into a laptop computer.

(See the printed Quick Installation Guide included with the DWL-G650.)



Install the drivers for the D-Link DFE-530TX wireless Cardbus adapter into a desktop computer. The four Ethernet LAN ports of the DI-624 are Auto MDI/MDIX and will work with both Straight-Through and Cross-Over cable. (See the printed Quick Installation Guide included with the DFE-530TX.) 13

After you have completed the Setup Wizard (please see the Quick Installation Guide that came with the product) you can access the Configuration menu at any time by opening the web browser and typing in the IP Address of the DI-624. The DI-624 default IP Address is shown below:

- Open the web browser
- Type in the IP Address of the Router

ţ.	ţdž	\$5mm	Favoritas	Taaja	13ala
0	flach.	- 0			6
Agan	10	http:	//192.168	3.0.1	

Note: if you have changed the default IP Address assigned to the DI-624, make sure to enter the correct IP Address.

- Type admin in the User Name field
- Leave the Password blank
- Click Next


Connect to :	192.168.0.1	? 🛛
R		
Access Point User name:	😰 admin	~
Password:	Remember my passwor	d
	ок	Cancel

The **Home>Wizard** screen will appear. Please refer to the *Quick Installation Guide* for more information regarding the Setup Wizard.



Home > W	lireless				
D-Lin					
	High-Speed 2.4GHz Wireless Router				
DI-624	Home Advanced Tools Status Help				
	Wireless Settings These are the wireless settings for the AP(Access Point)Portion.				
Wizard	SSID : default				
Wireless	Channel: 6 M WEP: C Enabled @ Disabled				
	WEP Encryption: 64Bt •				
WAN	Kay Type: [HEX] Kay1: # [000000000				
LAN	Key2: C 000000000				
	Key3: © 000000000 Key4: © 000000000				
1 DHCP	Solution (1997) Apply Cancel Help				
SSID-	Service Set Identifier (SSID) is the name designated for a s cific wireless local area network (WLAN). The SSID's fac default setting is default . The SSID can be easily changed connect to an existing wireless network or to establish a r wireless network.	tory d to			
Channel-	6 is the default channel. All devices on the network must sh the same channel. (<i>Note: The wireless adapters will autom</i> <i>cally scan and match the wireless setting.</i>)				
WEP-	Wired Equivalent Privacy (WEP) is a wireless security proto for Wireless Local Area Networks (WLAN). WEP provides se rity by encrypting the data that is sent over the WLAN. Se Enabled or Disabled . Disabled is the default setting. (Not you enable encryption on the DI-624 make sure to also ena encryption on all the wireless clients or wireless connection not be established.)	ecu- lect e: If able			
WEP Encryption-	Select the level of encryption desired: 64-bit, or 128-bit				
Кеу Туре-	Select HEX or ASCII				
Passphrase-	When you select Key Type: ASCII , you can enter a Passphr for any or all of Keys 1-4	ase			
Keys 1-4-	Input up to 4 WEP keys; select the one you wish to use.				
Apply-	Click Apply to save the changes.	5			

Home > WAN > Dynamic IP Address



Dynamic IP Address-	Choose Dynamic IP Address to obtain IP Address information automatically from your ISP. Select this option if your ISP does not give you any IP numbers to use. This option is commonly used for Cable modem services.
Host Name-	The Host Name is optional but may be required by some ISPs. The default host name is the device name of the Router and may be changed.
MAC Address-	The default MAC Address is set to the WAN's physical inter- face MAC address on the Broadband Router. It is not recom- mended that you change the default MAC address unless re- quired by your ISP.
Clone MAC Address-	The default MAC address is set to the WAN's physical interface MAC address on the Broadband Router. You can use the "Clone MAC Address" button to copy the MAC address of the Ethernet Card installed by your ISP and replace the WAN MAC address with the MAC address of the router. It is not recommended that you change the default MAC address unless required by your ISP.
Apply-	Click Apply to save the changes.

Home > WAN > Static IP Address

	Property lies	-	The second s	Contraction of the	-
Ho	me Adve	anced	Tools	Status	Help
WAN S Please	select the appropr	iate option f	a cannect to y	your ISP.	
O Dy	ramic IP Address			oobtain an IP address nost Cable modern us	
🛞 Sta	tic IP Address		e this option to your ISP.	oset static IP informat	ion provided b
O PP	PoE	Choose DSL ut		yaur ISP uses PPPat	i (Far mast
0.08	ers	PPTP	and BigPond I	Cable	
	O PPTP	for Eu	rope use only)		
Static	P				
IP Addr	855	0.0.00	1	(assigned by your ISP	カ
Subnet	Mask	0.0.0.0	6		
ISP Ga	teway Address	0.0.0.0	1		
Primary	DNS Address	0.0.00			
Second	ary DNS Address	0.0.00		(optional)	

Static IP Address-Choose Static IP Address if all WAN IP information is provided to you by your ISP. You will need to enter in the IP address, subnet mask, gateway address, and DNS address(es) provided to you by your ISP. Each IP address entered in the fields must be in the appropriate IP form, which are four octets separated by a dot (x.x.x.x). The Router will not accept the IP address if it is not in this format.

IP Address- Input the public IP Address provided by your ISP

Subnet Mask- Input your Subnet mask. (All devices in the network must have the same subnet mask.)

ISP

Gateway Address- Input the public IP address of the ISP to which you are connecting

Primary DNS Address-

ddress- Input the primary DNS (Domain Name Server) IP address provided by your ISP

Secondary DNS Address- This is optional

Apply- Click Apply to save the changes.



Please be sure to remove any existing PPPoE client software installed on your computers.

Choose *PPPoE* (Point to Point Protocol over Ethernet) if your ISP uses a PPPoE connection. Your ISP will provide you with a username and password. This option is typically used for DSL services. Select *Dynamic PPPoE* to obtain an IP address automatically for your PPPoE connection. Select *Static PPPoE* to use a static IP address for your PPPoeE connection.

Home Advo	nced 1	ols	Status	Help
Please addret the appropria	de aptien to pole	eest to pick	197	
C Dynamic P Address	Chantaithe I	option to of P. (For mar	tals at Place Code score	net with alcal
C State P Addess	1	spine to to		rutise posided
() PPPoE			er EP nim PF	Pall. Fir and
C Obre	PPTP and G	PeedCal	÷	
C PP(P	(he Europe a	an wiki		
perid				
	10 Dynamic	PPPhE (Static PPPa	e
Gaw Mervi	10000			
Perrout				
Retign Passwort	*******			
Seeille Merei			(in	tionall
H* Address	111.0	1		
Primary DME Address	DAAU			
Securitary Otto Address	DALU .	0	e ionisă	
Maximum Mis Time	10 Min	ant.		
HTU.	1482			
Adv excerned	(i) Dralled	OBrit	id .	

PPPoE-

Choose this option if your ISP uses PPPoE. (Most DSL users will select this option.)
Dynamic PPPoE- receive an IP Address automatically from your ISP.
Static PPPoE-you have an assigned (static) IP Address.
Your PPPoE username provided by your ISP.
Re-enter the PPPoE password
Enter the Service Name provided by your ISP (optional).
This option is only available for Static PPPoE. Enter the static IP Address for the PPPoE connection.
Primary DNS IP address provided by our ISP
This option is only available for Static PPPoE. Enter the static IP Address for the PPPoE connection.
The amount of time of inactivity before disconnecting your PPPoE session. Enter a Maximum Idle Time (in minutes) to define a maximum period of time for which the Internet connection is maintained during inactivity. If the connection is inactive for longer than the defined Maximum Idle Time, then the connection will be dropped. Either set this to zero or enable Auto-reconnect to disable this feature. <i>(Continued on the next page)</i> 18

Home > WAN > PPPoE

Using the Configuration Menu Home > WAN > PPPoE continued

MTU-		o change th			default setting performance	
Auto-reconnect-					connect to yo connection is	
Apply-	Click A	Apply to save	e the char	iges.		
Home > LAN						
D-Link Autor for header		High-Spee		Wireless Ro	uter	
	LAN Settings	Advanced	Tools	Status	Help	
	The IP address o	f the DI-624.				
Wizard	IP Address	192.188.0				
Wireless	Subnet Mask Local Domain Na	255.265.2	56.0			
	Local Coman Pa	1		Аррбу	(optional) S Cancel Help	
DHCP						

LAN is short for Local Area Network. This is considered your internal network. These are the IP settings of the LAN interface for the DI-624. These settings may be referred to as Private settings. You may change the LAN IP address if needed. The LAN IP address is private to your internal network and cannot be seen on the Internet.

IP Address-	The IP address of the LAN interface. The default IP add 192.168.0.1	ress is:
Subnet Mask-	The subnet mask of the LAN interface. The default subnet mask is 255.255.255.0	
Local Domain Name-	This field is optional. Enter in the local domain name.	
Apply-	Click Apply to save the changes.	19

_ . . . _ _

. .

OHCP Server The DF624 can be setup as a DHCP Server to distribute IP addresses to the D network. DHCP Server © Enabled © Disabled Starting IP Address 192. 168. 0. 100 Ending IP Address 192. 168. 0. 199 Lease Time 1 Wask T	Home	Advanc	ed To	ols	Status	He
DHCP Server @ Enabled C Disabled Starting IP Address 192, 168, 0, 100 Ending IP Address 192, 168, 0, 199 Lease Time 1 Wesk P	The DI-624 cas		DHCP Server t	o distribute l	P addresses to	the LAN
Starting IP Address 192.168.0.100 Ending IP Address 192.168.0.199 Lease Time T Wask 🖬		3	8 Enchlari ([*] Disphart		
Ending IP Address 192, 168, 0, 199 Lease Time 1 Wesk 📼	and another		Contractor -	100000		
Lease Time 🕴 🕐 🔮						
9 3	838.00 C.V.Y		and the second se			
DHCP Client Table						_
Host Name IP Address MAC Address Expired Time	DHCP Client.	Table			Apply	Cancel
unknown 192.168.0.101 00-50-BA-7D-E5-E1 Jan/03/2003 17:	Host Name I	P Address			Expired Tin	na

DHCP stands for *Dynamic Host Control Protocol*. The DI-624 has a built-in DHCP server. The DHCP Server will automatically assign an IP address to the computers on the LAN/ private network. Be sure to set your computers to be DHCP clients by setting their TCP/ IP settings to "Obtain an IP Address Automatically." When you turn your computers on, they will automatically load the proper TCP/IP settings provided by the DI-624. The DHCP Server will automatically allocate an unused IP address from the IP address pool to the requesting computer. You must specify the starting and ending address of the IP address pool.

DHCP Server-	Select Enabled or Disabled. The default setting is Enabled.
Starting IP Address-	The starting IP address for the DHCP server's IP assignment
Ending IP Address-	The ending IP address for the DHCP server's IP assignment
Lease Time-	The length of time for the IP lease. Enter the Lease time. The default setting is one hour
Apply-	click Apply to save the changes

Advanced > Virtual Server

24	-			GHz Wire		
	Home	Advanced	Too	ls S	tatus	Help
	Victual Server	and a subscription	nice and	CALCULATION OF	1.122.0.1	
	Virtual Server is	used to allow Interr	et users a	ccess to LAN se	anicas.	
		C Enabled C Di	sabled			
	Nama			Clea	r	
	Private IP	i	-	_		
	Protocol Type	TCP +				
	Private Port					
	Public Part					
	Schedule	C Always				
L.		C From time 00	• : 00	• AM • to 0	• 00 • 00	AM +
		day Bu	n • to 5	Sun ·		
			101010	1.0.2.1.2		
					0	3 6
L						
	Virtual Server	1.ht			Apply Co	mcel He
	Virtual Server		tivate IP	Protocol	Apply Co Schedu	
		F	mate IP 0.0.0	Protocol TCP 21/21		
	Name III Virtual Serv III Virtual Serv	nerFTP 0 nerHTTP 0	0.0.0 0.0.0	TCP 21/21 TCP 80/80	Schedu always always	e
	Name III Virtual Serv	nerFTP 0 nerHTTP 0	0.0.0	TCP 21/21	Schedul always	6

The DI-624 can be configured as a virtual server so that remote users accessing Web or FTP services via the public IP address can be automatically redirected to local servers in the LAN (Local Area Network).

The DI-624 firewall feature filters out unrecognized packets to protect your LAN network so all computers networked with the DI-624 are invisible to the outside world. If you wish, you can make some of the LAN computers accessible from the Internet by enabling *Virtual Server*. Depending on the requested service, the DI-624 redirects the external service request to the appropriate server within the LAN network.

Using the Configuration Menu Advanced > Virtual Server continued

The DI-624 is also capable of port-redirection meaning incoming traffic to a particular port may be redirected to a different port on the server computer.

Each virtual service that is created will be listed at the bottom of the screen in the Virtual Servers List. There are pre-defined virtual services already in the table. You may use them by enabling them and assigning the server IP to use that particular virtual service.

Virtual Server-	Select Enabled or Disabled
Name-	Enter the name referencing the virtual service
Private IP-	The server computer in the LAN (Local Area Network) that will be providing the virtual services.
Protocol Type-	The protocol used for the virtual service
Private Port-	The port number of the service used by the Private IP computer
Public Port-	The port number on the WAN (Wide Area Network) side that will be used to access the virtual service.
Schedule-	The schedule of time when the virtual service will be enabled. The schedule may be set to Always , which will allow the particular service to always be enabled. If it is set to Time , select the time frame for the service to be enabled. If the system time is outside of the scheduled time, the service will be disabled.

Apply- Click Apply to save the changes.

Example #1: If you have a Web server that you wanted Internet users to access at all times, you would need to enable it. Web (HTTP) server is on LAN (Local Area Network) computer 192.168.0.25. HTTP uses port 80, TCP. Name: Web Server Private IP: 192.168.0.25 Protocol Type: TCP Private Port: 80 Public Port: 80 Schedule: always

Using the Configuration Menu Advanced > Virtual Server *continued*

Virtual Servers List

	Name	Private IP	Protocol	Schedule	
R	Virtual Server HTTP	192.168.0.25	TCP 80/80	always	



Click on this icon to edit the virtual service

Click on this icon to delete the virtual service

Example #2:

If you have an FTP server that you wanted Internet users to access by WAN port 2100 and only during the weekends, you would need to enable it as such. FTP server is on LAN computer 192.168.0.30. FTP uses port 21, TCP.

Name: FTP Server Private IP: 192.168.0.30 Protocol Type: TCP Private Port: 21 Public Port: 2100

Schedule: From: 01:00AM to 01:00AM, Sat to Sun

All Internet users who want to access this FTP Server must connect to it from port 2100. This is an example of port redirection and can be useful in cases where there are many of the same servers on the LAN network.

Advanced > Applications

Ho	me Adv	anced	Tools	Status	Help
	Application				
Special	Application is us	ed to run app	lications that req	uire multiple conne	ctions.
	C Ena	bled C Disa	bled		
Name				Clear	
Trigger	Port	1.			
Trigger	TYPE TOP				
Public P	hor		50		
Public 1	ype TCP -	3			
		~		60	00
· Karda	Applications L	lat.			Cancel He
NAN	C. C. M. M. C. L. C.	Trigger Public		Аррту	conces ne
T Batt		6112 6112			
III Dial			0-51201,51210		
I ICU				51,2069,2085,301	10-3030 📃
			-2400,28800-2		
F PC-	to-Phone	120531212 554 6970	0,12122,24150	24220	

Some applications require multiple connections, such as Internet gaming, video conferencing, Internet telephony and others. These applications have difficulties working through NAT (Network Address Translation). Special Applications makes some of these applications work with the DI-624. If you need to run applications that require multiple connections, specify the port normally associated with an application in the "Trigger Port" field, select the protocol type as TCP or UDP, then enter the public ports associated with the trigger port to open them for inbound traffic.

The DI-624 provides some predefined applications in the table on the bottom of the web page. Select the application you want to use and enable it.

Note! Only one PC can use each Special Application tunnel.

Name:	This is the name referencing the special application.			
Trigger Port:	This is the port used to trigger the application. It can be a single port or a range of ports.	either		
Trigger Type:	This is the protocol used to trigger the special applicati	on.		
Public Port:	This is the port number on the WAN side that will be us access the application. You may define a single port or range of ports. You can use a comma to add multiple port ranges.	a		
Public Type:	This is the protocol used for the special application.			
Apply:	Click Apply to save the changes	24		

Advanced > Filters > IP Filters

nk			ed 2.4GHz V	and the second se	
	Home	Advanced	Tools	Status	Help
	Filters are used to	to allow or deny LAN	users from access	ing the Internet.	
	@ P Fiters	C URL Blockin			
	e contra	C Domain Bloc	-		
	IP Filters Use IP Filters to	deny LAN IP addres	ses access to the	internet.	
	C Enabled C	Disabled Clear			
		P	-	1	
	1	Port			
	Protocol T	ура ТСР			
		dule C Always			
			• : 00 • AM	to 00 • : 00	* AM *
		day Sun	- to Sun -		
				1	3 C
	IP Filler List				Cancel Hel
	the second second second second				
	IP Rang	e Protoco TCP 20		Schedule always	171

Filters are used to deny or allow LAN (Local Area Network) computers from accessing the Internet. The DI-624 can be setup to deny internal computers by their IP or MAC addresses. The DI-624 can also block users from accessing restricted web sites.

IP Filters	Use IP Filters to deny LAN IP addresses from accessing the Internet. You can deny specific port numbers or all ports for the specific IP address.
IP:	The IP address of the LAN computer that will be denied access to the Internet.
Port:	The single port or port range that will be denied access to the Internet.
Protocol Type:	Select the protocol type
Schedule:	This is the schedule of time when the IP Filter will be enabled.
Apply:	Click Apply to save changes.

Advanced > Filters > URL Blocking



URL Blocking is used to deny LAN computers from accessing specific web sites by the URL. A URL is a specially formatted text string that defines a location on the Internet. If any part of the URL contains the blocked word, the site will not be accessible and the web page will not display. To use this feature, enter the text string to be blocked and click **Apply.** The text to be blocked will appear in the list. To delete the text, just highlight it and click **Delete**.

Filters-	Select the filter you wish to use; in this case, URL Blocking was chosen.
URL Blocking-	Select Enabled or Disabled.
Keywords-	Block URLs which contain keywords listed below. Enter the keywords in this space.
Apply-	Click Apply to save the changes.

Advanced > Filters > MAC Filters

24			-		
	Home	Advanced	Tools	Status	Help
	iters are used to	allow or deny LAN	users from acces	sing the Interne	e1,
	D IP Filters	O URL Blackie			
	MAC Filters		*		
1	AC Filtern				
		s to allow or deny c	impluters access	to the network.	
	Disphart MAC	Elters			
	Disabled MAC	C Filters omputers with MAC	address listed by	low to access t	the network
	Only allow c				
	 Only allow c Only deny co 	omputers with MAC			
	Only allow c Only deny co Nar	emputers with MAC mputers with MAC me_MAC filter 1	address listed be	ow to access the Cleer	
	 Only allow c Only deny co 	omputers with MAC mputers with MAC me_MAC filter 1	address listed be	ow to access the Cleer	
	Only allow c Only deny co Nar MAC Addre	emputers with MAC mputers with MAC me_MAC filter 1	address listed be	ow to access the Cleer	
	Only allow c Only deny co Nar MAC Addre	omputers with MAC mputers with MAC me MAC filter 1 ss 00 _ 80 _	address listed be	ow to access the Cleer	
	Only allow c Only deny co Nar MAC Addre	omputers with MAC mputers with MAC me MAC filter 1 ss 00 _ 80 _	address listed be	ow to access the Cleer	

Use MAC (Media Access Control) Filters to allow or deny LAN (Local Area Network) computers by their MAC addresses from accessing the Network. You can either manually add a MAC address or select the MAC address from the list of clients that are currently connected to the Broadband Router.

Filters-	Select the filter you wish to use; in this case, MAC filters was chosen.
MAC Filters-	Choose Disable MAC filters; allow MAC addresses listed below; or deny MAC addresses listed below.
Name-	Enter the name here.
MAC Address-	Enter the MAC Address.
DHCP Client-	Select a DHCP client from the pull-down list; click $\ensuremath{\textbf{Clone}}$ to copy that MAC Address
Apply-	Click Apply to save the changes.

Advanced > Filters > Domain Blocking



Domain Blocking is used to allow or deny LAN (Local Area Network) computers from accessing specific domains on the Internet. Domain blocking will deny all requests to a specific domain such as http and ftp. It can also allow computers to access specific sites and deny all other sites.

Filters-	Select the filter you wish to use; in this case, Domain Blocking
Domain Blocking:	was chosen.
Disabled-	Select Disabled to disable Domain Blocking
Allow-	Allows users to access all domains except Blocked Domains
Deny-	Denies users access to all domains except Permitted Domains
Permitted Domains-	Enter the Permitted Domains in this field
Blocked Domains-	Enter the Blocked Domains in this field
Apply-	Click Apply to save the changes. 28

Advanced > Firewall

	and a second	No. of Concession, Name	-	The other designation of the other designation
Hor	ne Advanced	Tools	Status	Help
Firewall Firewall	Nales Rules can be used to allow	or deny traffic fe	im pessing through t	the D1-624.
	C Enabled C Disabl	ed		
Nama		Clear		
Action	C Allow C Dany	1453		
	Interface IP Range Sta	rt IP Range B	End Protocol P	ort Range
Source	• =	_		
Destinati	on * 💌		TCP -	- D+
Schedule	C Always			
	C From time 00 💽 : day Bun 💌 Pulee List	to Bun 💌		😕 🔂
Actio	 Name Allow to Ping WAN por 	Bource	Destination LAN, 192, 168, 0, 1	Protocol ICMP.B
E Dany		•••	LAN, 192 168 UT	iP(0),"
	L'ATRIAT.	LAN."	manda"	IP (0).*

Firewall Rules is an advanced feature used to deny or allow traffic from passing through the DI-624. It works in the same way as IP Filters with additional settings. You can create more detailed access rules for the DI-624. When virtual services are created and enabled, it will also display in Firewall Rules. Firewall Rules contain all network firewall rules pertaining to IP (Internet Protocol).

In the Firewall Rules List at the bottom of the screen, the priorities of the rules are from top (highest priority) to bottom (lowest priority.)

Note: The DI-624 MAC Address filtering rules have precedence over the Firewall Rules.

Firewall Rules-	Enable or disable the Firewall
Name-	Enter the name
Action-	Allow or Deny
Source-	Enter the IP Address range
Destination-	Enter the IP Address range ; the Protocol ; and the Port Range
Schedule-	Select Always or enter the Time Range.
Apply-	Click Apply to save the changes.


Advanced > DMZ



If you have a client PC that cannot run Internet applications properly from behind the DI-624, then you can set the client up for unrestricted Internet access. It allows a computer to be exposed to the Internet. This feature is useful for gaming purposes. Enter the IP address of the internal computer that will be the DMZ host. Adding a client to the DMZ (Demilitarized Zone) may expose your local network to a variety of security risks, so only use this option as a last resort.

DMZ-	Enable or Disable the DMZ. The DMZ (Demilitarized Zone) allows a single computer to be exposed to the internet. By default the DMZ is disabled .
IP Address-	Enter the IP Address of the computer to be in the DMZ
Apply-	Click Apply to save the changes.

Advanced > Performance



Wireless Performance-

Displayed in this window are the Wireless Performance features for the Access Point portion of the DI-624.

Beacon Interval-	Beacons are packets sent by an Access Point to synchronize a wireless network. Specify a value. 100 is the default setting and is recommended.
RTS Threshold-	This value should remain at its default setting of 2432. If inconsistent data flow is a problem, only a minor modification should be made.
Fragmentation-	The fragmentation threshold, which is specified in bytes, deter- mines whether packets will be fragmented. Packets exceeding the 2346 byte setting will be fragmented before transmission.2346 is the default setting
DTIM interval-	(Delivery Traffic Indication Message) 3 is the default setting. A DTIM is a countdown informing clients of the next window for listening to broadcast and multicast messages.
Preamble Type-	Select Short or Long Preamble . The Preamble defines the length of the CRC block (Cyclic Redundancy Check is a common technique for detecting data transmission errors) for communication between the wireless router and the roaming wireless network adapters. Auto is the default setting. <i>Note: High network traffic areas should use the shorter preamble type.</i>
Apply	Click Apply to cave changes

Apply-

Tools> Admin

Home	Advanced	Tools	Status	Help
Administrator	Sottings can change their login	password.		
Administrator (The Login Name is "ad	min")		
Naw	Password			
Confirm	Password -			
User (The Logi	n name is "user")			
Naw	Password -			
Continu	Password -			
Bassate Mana	gemunt -			
1/2		d ∉ Disabled		
1	Address *			
	Part 8080 •		-	-
			9	Cancel H

At this page, the DI-624 administrator can change the system password. There are two accounts that can access the Broadband Router's Web-Management interface. They are admin and user. Admin has read/write access while user has read-only access. User can only view the settings but cannot make any changes.

Administrator-	admin is the Administrator login name
Password-	Enter the password and enter again to confirm
User-	user is the User login name
Password-	Enter the password and enter again to confirm

Remote Management- Remote management allows the DI-624 to be configured from the Internet by a web browser. A username and password is still required to access the Web-Management interface. In general, only a member of your network can browse the built-in web pages to perform **Administrator** tasks. This feature enables you to perform Administrator tasks from the remote (Internet) host.

IP Address- The Internet IP address of the computer that has access to the Broadband Router. If you input an asterisk (*) into this field, then any computer will be able to access the Router. Putting an asterisk (*) into this field would present a security risk and is not recommended.

Port- The port number used to access the Broadband Router.

Example- http://x.x.x.x8080 where x.x.x.x is the WAN IP address of the Broadband Router and 8080 is the port used for the Web-Mangement interface.

Apply-

Tools > Time						
D-Link Intelling Verboordes for Progete		and the second second	Air Air A	Plus TREME Wireless Ro		
DI-624	Home	Advanced	Tools	Status	Help	2
Admin Time System Firmware Misc.	Time Bat the D4524 sy Local Time Time Zone Default NTP Serve Set the Time Daylight Saving	Dec/27/2002 17:3 ((SMT-08:00) Par er Vear 2002 M	inc Time (US & (optional) onth Dec • D te 31 • Seco Disabled	ay 27 • nd 61 • Set Tim	r Cancel Help	
Time Zone-	Select	the Time Zo	ne from th	e pull-down	menu.	_
Default NTP Server-	puter o		in a netwo	ne Protocol. I ork of compu	NTP synchro uters.	nizes com-
Set the Time-					llues in thes Second. Click	
Daylight Saving-					select enab date for dayl	
Apply-	Click A	pply to sav	e the cha	nges.		

Tools > System D-Link AirPlus TELEMIE High-Speed 2.4GHz Wireless Router DI-624 Advanced Status Home Tools Help System Settings Save Settings To Local Hard Drive Sme Load Settings From Local Hard Drive WE. System Load Firmware Restore To Factory Default Settings Restore o Help

The current system settings can be saved as a file onto the local hard drive. The saved file or any other saved setting file can be loaded back on the Broadband Router. To reload a system settings file, click on **Browse** to browse the local hard drive and locate the system file to be used. You may also reset the Broadband Router back to factory settings by clicking on **Restore**.

Save Settings to

Local Hard Drive- Click Save to save the current settings to the local Hard Drive


Load Settings from

Local Hard Drive- Click Browse to find the settings, then click Load

Restore to Factory

Default Settings- Click **Restore** to restore the factory default settings

Tools > Firmware



You can upgrade the firmware of the Router here. Make sure the firmware you want to use is on the local hard drive of the computer. Click on **Browse** to browse the local hard drive and locate the firmware to be used for the update. Please check the D-Link support site for firmware updates at http://support.dlink.com. You can download firmware up-grades to your hard drive from the D-Link support site.

Firmware Upgrade-Click on the link in this screen to find out if there is an updated
firmware; if so, download the new firmware to your hard drive.Browse-After you have downloaded the new firmware, click Browse in
this window to locate the firmware update on your hard drive.
Click Apply to complete the firmware upgrade.

Ping Test-

t- The Ping Test is used to send Ping packets to test if a computer is on the Internet. Enter the IP Address that you wish to Ping, and click **Ping**

Restart Device-Click Reboot to restart the DI-624

Block WAN Ping-

If you choose to block WAN Ping, the WAN IP Address of the DI-624 will not respond to pings. Blocking the Ping may provide some extra security from hackers.

Discard Ping from WAN side-

Click **Enabled** to block the WAN ping

Home	Advancer	Toes	Strain
Prog Taxt in constit	and They're	And in case of the	
Hed Banaus (F abless	-		1944
Name Inc.			
later			
When you Theat the out respect to a motion coupled by to	THE PART OF A	Inginational data (No.)	OFP addression
Disal PRO Nai	nna iai C a		
inst lange	*	C Duilei	
Internal Print	* case	f puese	
And Providence	the brank the	aut the India	
inte Plac		C Duikel	
0040		# Durited	
Titur Name	-		
1. Spenner 1	-		

UPNP- To use the *Universal Plug and Play* feature click on **Enabled**. UPNP provides compatibility with networking equipment, software and peripherals of the over 400 vendors that cooperate in the Plug and Play forum.

Gaming Mode-

Gaming mode allows a form of pass-through for certain Internet Games. If you are using XBOX, Playstation2 or a PC, make sure you are using the latest firmware and Gaming Mode is enabled. To utilize Gaming Mode, click **Enabled.** If you are not using a Gaming application, it is recommended that you **Disable** Gaming Mode.

Tools > Misc

D

Dynamic DNS-

Dynamic Domain Name System is a method of keeping a domain name linked to a changing IP Address. This is a useful feature since many computers do not use a static IP address.

VPN

Pass Through-The DI-624 supports VPN (Virtual Private Network) pass-through for both PPTP (Point-to-Point Tunneling Protocol) and IPSec (IP Security). Once VPN pass-through is enabled, there is no need to open up virtual services. Multiple VPN connections can be made through the DI-624. This is useful when you have many VPN clients on the LAN network.

PPTP- select Enabled or Disabled

IPSec- select Enabled or Disabled

Apply- Click Apply to save changes

Status > Device Info



This page displays the current information for the DI-624. It will display the LAN, WAN and MAC address information.

If your WAN connection is set up for a **Dynamic IP address** then a **Release** button and a **Renew** button will be displayed. Use *Release* to disconnect from your ISP and use *Renew* to connect to your ISP.

If your WAN connection is set up for **PPPoE**, a Connect button and a **Disconnect** button will be displayed. Use *Disconnect* to drop the PPPoE connection and use *Connect* to establish the PPPoE connection.

This window will show the DI-624's working status:

WAN

IP Address: WAN/Public IP Address Subnet Mask: WAN/Public Subnet Mask Gateway: WAN/Public Gateway IP Address Domain Name Server: WAN/Public DNS IP Address WAN Status: WAN Connection Status


LAN

IP Address: LAN/Private IP Address of the DI-624 Subnet Mask: LAN/Private Subnet Mask of the DI-624

Wireless

MAC Address: Displays the MAC address SSID: Displays the current SSID Channel: Displays the current channel WEP: indicates whether WEP is enabled or disabled

Status > Log




The Broadband Router keeps a running log of events and activities occurring on the Router. If the device is rebooted, the logs are automatically cleared. You may save the log files under Log Settings.

View Log-

First Page - The first page of the log Last Page - The last page of the log Previous - Moves back one log page Next - Moves forward one log page Clear - Clears the logs completely Log Settings - Brings up the page to configure the log

Status > Log > Log Settings



Log Settings-

Not only does the Broadband Router display the logs of activities and events, it can setup to send these logs to another location.

SMTP Server/IP Address - The address of the SMTP server that will be used to send the logs

Email Address - The email address to which the logs will be sent. Click on **Send Mail Now** to send the email.

Click **Apply** to save the changes.

Status > Stats



The screen above displays the Traffic Statistics. Here you can view the amount of packets that pass through the DI-624 on both the WAN and the LAN ports. The traffic counter will reset if the device is rebooted.

Status > Wireless

		ed 2.4GHz	. miretess n	touter	
ne	Advanced	Tools	Status	Н	elo
Paint).	it table below disp	ays withess ca	ems conhected to	o the Ap	Hel
d Time		MAC Addres	100	Mode	
Paint).	it table below disp	120010000000			

The wireless client table displays a list of current connected wireless clients. This table also displays the connection time and MAC address of the connected wireless client.

Click on **Help** at any time, for more information.