P-660HW-T v2

802.11g Wireless ADSL 2+ 4-port Gateway

Quick Start Guide

Version 3.40 6/2006 Edition 1



Overview

The P-660HW-T v2 is an ADSL router with a four-port built-in Ethernet switch and IEEE 802.11b/g wireless capability. The P-660HW-T v2 allows wired and wireless clients to safely access the Internet.

See your User's Guide for background information on all features.


How to use the included CD

This CD provides multi-media animations that help you set up your P-660HW-T v2.

- 1 On the included CD, click Multimedia Auto Provisioner > Installation Tutorial.
- 2 At the end of the tutorial, click Configuration Genie.

1 Hardware Connections

If you prefer to see a multi-media animation of how to make hardware connections, see the installation tutorial on the included CD.




1 DSL: Use a telephone wire to connect your P-660HW-T v2's DSL port to a telephone jack (or to a splitter, if one is already installed).

- 2 ETHERNET: Use an Ethernet cable to connect a computer to an ETHERNET port for initial configuration and/or Internet access.
- **3 POWER**: Use the power adaptor provided with your P-660HW-T v2 to connect an appropriate power source to the **POWER** socket. Make sure the power source is on.
- **4** Push in the **POWER** button. Look at the lights on the front panel.
- The POWER light blinks while your P-660HW-T v2 starts up and stays on once it is ready. The DSL light is on
 when the P-660HW-T v2 has a DSL connection, and the WLAN light is on when the wireless LAN is ready. The
 INTERNET light is on when you are able to access the Internet and blinks when the P-660HW-T v2 is sending
 or receiving data.
- Each ETHERNET light stays on if the corresponding ETHERNET port is properly connected and blinks when there is traffic.

If any of these lights are not on, check your connections, and inspect your cables for damage. If the lights are still off, contact your local vendor.

2 Status Page

1 In your browser, go to http://192.168.1.1.



If your browser cannot find this screen, check its security settings. See **Troubleshooting** for details.





ZyXEL 7 9 > Status Refresh Interval: None Apply Status Device Information System Status -660HW-T3 v2 Host Name: P-660HW-T3 v2 System Uptime: P-660HW-T3 v2 01/01/2000 00:08:48 Current Date/Time: Model Number: MAC Address: 00:13:49:45:a4:ad System Mode: Routing / Bridgin ZyNOS Firmware Version: V3.40(ANR.0)b3 | 06/13/2006 CPILUsane: 8.78% WAN Information 27% Memory Usage: - DSI Mode: Error - IP Address: 0.0.0.0 - IP Subnet Mask: 0.0.0.0 Interface Status - Default Gateway: 0.0.0.0 - VPI/VCI: 8/35 LAN Information 192.168.1.1 - IP Address: Down 0 kbps / 0 kbps - IP Subnet Mask: 255.255.255.0 LAN Up 100M/FullDuplex - DHCP: WLAN Information WLAN 54M Active ZVXEL - SSID: - Channel: Disable - Security:

3 See the User's Guide for field descriptions of the Status screen.

3 Internet and Wireless Setup


Message Ready

1 Open your web browser, and go to http://www.zyxel.com.

Your P-660HW-T v2 tries to detect your Internet connection. Wait for the P-660HW-T v2 to finish detection. If any other screens appear, follow the directions in the screen.

If the web page opens correctly, your P-660HW-T v2 is ready for you to use. If the web page does not open, follow the rest of the steps. You should have the information provided by your ISP.

2 In your browser, go to http://192.168.1.1.



3 Enter the admin password 1234 to set up your internet and wireless connections and security settings. Click Login. If your browser cannot find the login screen, check its security settings. See Troubleshooting for details. 4 Follow the directions in the screens.



- 5 Click Go to Wizard setup. Then, click Apply.
- 6 Click INTERNET/WIRELESS SETUP. Wait while your P-660HW-T v2 tries to detect your DSL connection.



7 Follow the directions in the wizard. Do not change default settings if your ISP did not provide information.

OTIST

ZyXEL's One-Touch Intelligent Security Technology (OTIST) feature allows you to automatically configure the SSID and WPA-PSK on all OTIST-equipped wireless clients within range of the P-660HW-T v2.

Note: If you enable OTIST but select **Disable wireless security** using the wireless wizard, the P-660HW-T v2 will create a WPA-PSK automatically.

Enable OTIST only if your wireless clients support WPA and OTIST.

You must enable OTIST on the P-660HW-T v2 and all wireless clients (in any order) within three minutes.

To enable OTIST on the P-660HW-T v2, you can either use the wizard (see Section 3 on page 4) or hold in the **RESET** button (see Section 1 on page 2) for three to eight seconds. Do not hold the **RESET** button in for too long, as this will reset the P-660HW-T v2 to the factory defaults.

To enable OTIST on wireless clients, click **Start** in the **Adapter** screen. The **Setup Key** is 01234567 by default. If you have previously saved a setup key on the P-660HW-T v2, use it instead of the default.

For more information, see Wireless LAN in the User's Guide.

Troubleshooting

- 1 If you cannot access the web configurator using Internet Explorer in Windows XP or Windows Server 2003, make sure you allow pop-up windows, JavaScripts and Java permissions or set the Internet security level lower than **High** in Internet Explorer (in Internet Explorer, click **Tools > Internet Options > Security > Custom Level...**). See the appendix in the User's Guide for more information.
- 2 If you cannot access the Internet when your computer is connected to the **ETHERNET** port, follow these steps.
 - A) Check the lights on the front panel. If they are different from what is described in section 1, make sure the P-660HW-T v2 is correctly connected. (See section 1.) If the lights are still different, turn off the device, wait a few seconds, and turn it on again.
 - **B)** Follow the steps in section 3 again. Make sure you enter the correct information. For example, if your account has a user name and password, make sure you type it correctly. In addition, if you are not sure which encapsulation your ISP uses, contact your ISP.
 - **C)** If you are using a new Internet account, contact your ISP to make sure it is active.
 - **D)** If you still have problems, see **Troubleshooting** in the User's Guide.
- **3** If you cannot access the Internet using the wireless network, follow these steps.
 - A) On a computer in the wireless network, open your browser, and go to http://192.168.1.1. If you see the screen in step 3 of section 3, follow suggestions A D above. If you do not, go to the next step.
- **B)** Make sure your P-660HW-T v2 and your computer are using the same wireless and wireless security settings. Follow the steps in section 3.

Viewing Your Product's Certifications

- 1 Go to www.zvxel.com.
- 2 Select your product from the drop-down list box on the ZyXEL home page to go to that product's page.
- **3** Select the certification you wish to view from this page.